


Green Pin® Tapered Pin ROV Release & Retrieve Shackle with Fishtail Handle – GPROV5361F, Grade 8 Offshore Subsea Polar Shackle

Material: Grade 8 polar quality alloy steel body and pin, quenched and tempered.
Finish: White painted body and green painted pin.
Safety Factor: Minimum breaking load is 5 times the W.L.L.
Temperature Range: Temperature range -60°C up to +200°C.
Additional Information: Supplied without wires; design your own wiring plan.



SPECIFICATION

Product Code	WLL (t)	A (mm)	B (mm)	C (mm)	D (mm)	E (mm)	F (mm)	G (mm)	H (mm)	I (mm)	J (mm)	K (mm)	Weight (kg)
GPROV5361F6.5	6.5	22	25	52	22	36	83	58	144	419	102	3.5	1.5
GPROV5361F9.5	9.5	28	32	66	28	47	108	75	185	455	131	5.5	3.16
GPROV5361F12	12	32	35	72	32	51	115	83	201	467	147	6.5	4.31
GPROV5361F17	17	38	42	88	38	60	146	99	249	491	175	8.5	7.43
GPROV5361F25	25	45	50	103	45	74	178	126	300	538	216	8.5	12.84
GPROV5361F35	35	50	57	111	50	83	197	138	331	558	238	8.5	18.15
GPROV5361F42.5	42.5	57	65	130	57	95	222	160	377	590	274	7.5	26.29
GPROV5361F55	55	65	70	145	65	105	260	180	433	619	310	7.5	37.6